



LG 20" Slim, new design computer monitor 51 cm (20.1") 1600 x 1200 pixels Silver



Brand : LG

Product code: L2000C-SF

Product name : 20" Slim, new design

20.1" Active Matrix TFT LCD Monitor

LG 20" Slim, new design computer monitor 51 cm (20.1") 1600 x 1200 pixels Silver:

Highlights: The LG FLATRON™ L2000c 20.1" LCD Display is the choice for graphics-intensive applications. It boasts an 8-BIT, 16.8M COLOR, 8MS RESPONSE, 1600x1200 RESOLUTION display which outputs crisp, distortion-free images. The integrated f-ENGINE™ allows for independent adjustments of contrast and brightness, useful for viewing multimedia. The monitor adjustments are easily accessible on the Ultra Thin front bezel and the ergonomic design allow for TILT, PIVOT, SWIVEL, and HEIGHT ADJUST functions. The enhanced productivity and ease of use makes the FLATRON™ L2000C ideal for graphics, medical, and financial professionals.

LG 20" Slim, new design. Display diagonal: 51 cm (20.1"), Display resolution: 1600 x 1200 pixels, Response time: 8 ms, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Product colour: Silver

Display		Ports & interfaces	
Surface treatment	Anti-glare, Hard coating(3H)	Audio output	✗
Display diagonal *	51 cm (20.1")	Ergonomics	
Display resolution *	1600 x 1200 pixels	Swivel angle range	350
Touchscreen *	✗	Tilt angle range	5 - 20°
Display brightness (typical)	300 cd/m ²	Ergonomics	ISO 13406-2
Response time *	8 ms	Power	
Contrast ratio (typical) *	800:1	Power consumption (typical) *	58 W
Viewing angle, horizontal	178°	Power consumption (standby) *	2 W
Viewing angle, vertical	178°	Weight & dimensions	
Pixel pitch	0.255 x 0.255 mm	Width (without stand)	446 mm
Horizontal scan range	28 - 92 kHz	Depth (without stand)	223 mm
Vertical scan range	56 - 85 Hz	Height (without stand)	445.6 mm
Viewable size, horizontal	40.8 cm	Other features	
Viewable size, vertical	30.6 cm	Power requirements	AC 90~264 V (47 ~ 63Hz), LIPS
Digital horizontal frequency	28 - 80 kHz	Display viewable area (HxV)	408 x 306 mm
Design		Safety	UL,cUL,TUV-GS,SEMCO
Product colour *	Silver	Interface	LVDS
Ports & interfaces		Mean time between failures (MTBF)	50000 h
VGA (D-Sub) ports quantity	1	Power management	EPA Energy Star
DVI port	✓	Certification	VCCI-2 (Japan),C-TICK (Australia),GOST (Russia),TCO-03,FCC-B,CE.
DVI-D ports quantity	1		
Audio input	✗		

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.